

The complete guide to the set/registry portal

Browsing the catalogue, reading evidence and scores, comparing and downloading sets, collecting baskets, building portfolios, uploading and publishing your own parameter files, managing your account, and the operator console.

Contents

- 1. The Platform At A Glance
- 2. Getting Started
- 3. Accounts, Sign-In, And Security
- 4. Your Account Area
- 5. Browsing The Catalogue
- 6. Set Pages
- 7. Reconstructed Report Pages
- 8. Comparing Set Versions
- 9. Downloading
- 10. Uploading And Publishing Sets
- 11. Portfolios
- 12. Creators And Brokers
- 13. Notifications
- 14. Scores, Methodology, And Trust
- 15. Error Pages And Limits
- 16. The Operator Console (Administration)
- Appendix: Glossary

This manual describes every feature of **set/registry**, the independent community library for parameter `.set` files. It walks through browsing and filtering the catalogue, reading evidence, metrics and scores, comparing and downloading sets, collecting download baskets, building portfolios, uploading and publishing your own files, managing your account, and using the moderation and operator tooling.

The portal is a factual library, nothing more: it never recommends sets, never ranks by popularity by default, and never presents historical test data as a forecast. Where this manual describes warnings and confirmations, those texts are part of how the platform works — they are quoted or paraphrased from the product itself.

1. The Platform At A Glance

1.1 What set/registry is

set/registry is a free community library for user-created parameter `.set` files intended for use with the Ultimate Breakout System Expert Advisor for MetaTrader 5. Uploaders publish parameter files, optionally together with MetaTrader 5 backtest reports as evidence. The portal parses those reports deterministically, reconstructs historical metrics from the underlying deals, flags structural risks, and shows the provenance of every published number.

Three principles shape everything you see:

- **No advice and no recommendations.** The catalogue is ordered by publication date (newest first) by default. There are no leaderboards, no featured sets, no suitability labels. Sorting by metrics or downloads exists, but the portal labels it explicitly as *your own filter*, not a recommendation.
- **Immutable provenance.** Published set files, parsed reports, metric snapshots and score definitions are versioned and immutable. A correction never rewrites history — it creates a new version, and the old version stays visible.
- **Free and account-free downloads.** Downloading requires no registration and no payment. Downloads are gated only by a risk acknowledgement and the current legal documents.

The portal is an independent service. It is not affiliated with, endorsed by, or associated with the developer or publisher of Ultimate Breakout System, MetaQuotes Ltd., MetaTrader 5, any broker, or UBS Group AG. Nothing on the portal is financial, investment, trading, tax, or legal advice. Trading can cause substantial or total loss.

1.2 What is public and what stays private

Public	Private (never published)
Approved <code>.set</code> file bytes and metadata	Original MT5 reports (HTML/XLSX)

Public	Private (never published)
Sanitised reconstructions of parsed reports	Supporting images
Metric and score snapshots with provenance	Your email address
Username, public profile, version history	Unpublished drafts and quarantined files

Original reports stay on the server and are never included in public downloads or basket ZIPs. Only sanitised reconstructions are shown on public pages.

2. Getting Started

— 2.1 First visit — no account needed

Browsing, comparing, and downloading all work without an account:

1. Open the catalogue from **Catalogue** in the header.
2. Filter or search until you find a set, then open its set page.
3. Read the risk flags, metrics, and evidence sections.
4. Choose **Download .set** and accept the download disclosure, or add the version to the **Download basket** and download several versions as one ZIP.

— 2.2 Creating an account

An account is only needed to upload sets, build portfolios, keep favourites and notification rules, and manage your public profile. Registration requires:

- an email address and a public username (3–30 characters; letters, digits, underscore, hyphen),
- a password of at least 12 characters,
- the age declaration (legal age or parental consent, lawful use),
- acceptance of the current Terms, Risk Disclosure, and other required documents (shown with their version numbers),
- optional, separate, double-opt-in consent to a daily email with new sets matching your filters.

After registration you receive a verification email; open the link before signing in. Your email stays private — your username, profile, published sets, version history, and counted downloads are public. The registration page warns you explicitly to use a pseudonym and not to publish personal data.

— 2.3 Navigation map

The header gives you: **Catalogue**, **Compare**, **Creators**, **Methodology**, **Portfolios** (when the feature is enabled), the global **search** with typeahead suggestions (sets, creators, symbols, brokers), **Upload set**, the **Download basket** with an item counter, your **language switch** (English/Deutsch), and the **account menu** (sign in / account / sign out). The footer collects policies and processes: legal documents, About, Help, Contact, Status, the **Platform manual (PDF)** — the document you are reading, also linked from the Help page — Report content, and Appeals.

3. Accounts, Sign-In, And Security

— 3.1 Signing in

Sign in with email and password, or with a **passkey**: on the sign-in page choose *Sign in with a passkey* and use the passkey stored on your device, another device, or a security key — no password needed. If your device does not offer the passkey, enter your email address first and try again (the portal uses the email to select the right account).

— 3.2 Forgot password

Use **Forgot password?** and enter your account email. If the address can receive a reset link, instructions are sent. The response is deliberately identical whether or not the address is registered. A completed reset signs out all other sessions.

— 3.3 Email verification

Before you can sign in, verify your address with the link from the verification email. If the message does not arrive, use *Resend verification email* (also subject to the same "identical response" rule) and check your spam folder.

— 3.4 Passkeys and sessions (Account → Security)

- **Passkeys**: add one or more, each with a name (e.g. "personal laptop"). The list shows device type (single- or multi-device), whether the passkey is synced/backed up, transports (USB, NFC, Bluetooth, cross-device, built-in), creation date and last use. Renaming and revoking are supported. Privileged accounts must keep an active passkey — the last one cannot be revoked until another is added. Your email must be verified before adding a passkey.
- **Password change**: requires your current password; other sessions stay controlled by you.
- **Active sessions**: lists signed-in devices with creation date, last activity, and an approximate country code. Revoke individual sessions or all other devices. A password change or passkey change securely renews your current session.
- **Step-up verification**: sensitive actions (and the whole admin area) can require a fresh passkey verification even while signed in.

4. Your Account Area

The account area under **Account** offers:

- **Overview** — published sets, drafts in progress, counted downloads, followers/following, active notification rules, and a pointer to uploads that need action.
- **My sets** — everything you have published, with links to each set and version.
- **Favourites** — sets you favourited and creators you follow, for quick access.
- **Upload batches** — private server-backed drafts. Resume an unfinished upload from any browser where you are signed in, or remove it: removing an unpublished batch cancels the upload and discards its files; published sets are never affected.
- **Notification rules** — see chapter 13.
- **Profile & privacy** — display name and a short factual bio (no offers, links, or advice). Usernames can be changed after a cooldown period; the previous username stays reserved so history cannot be hijacked.
- **Security & passkeys** — see chapter 3.4.
- **Data export & deletion** — request a machine-readable export of your account data. Deletion removes your public profile promptly and schedules removal of personal data. You can choose to keep published sets under a neutral "Former member" attribution (no personal data); otherwise they leave future distribution. Deletion can be cancelled until its execution date.

5. Browsing The Catalogue

5.1 Search

The catalogue search accepts title, creator, symbol, broker, and hash prefix. The header search suggests matching sets, creators, symbols, and brokers as you type.

5.2 Sorting — and what it means

The default order is **newest publications first**. You can switch to oldest, title A–Z, counted downloads, any score, or a metric column (net return, max equity drawdown, profit factor, return-to-drawdown, trade count). The moment you sort by historical figures, the portal shows a standing warning: this is *your own filter*, not a recommendation, and the underlying data may be incomplete, unverifiable, or based on low-quality reports.

5.3 Filters

Group	Filters
Identity	Canonical symbol, raw broker symbol, timeframe, broker, uploader, source
Evidence	Evidence class (OHLC report, real-tick report, both, none), Evidence Confidence, RT History Quality (minimum %)
Periods	Publication date range, IS period range (with an explicit "unknown period" switch), OOS presence and period
Risk	Risk flags to require, risk flags to exclude (comma-separated keys)
Metrics	Min/max ranges for the metric columns, score ranges
Versions	Include superseded versions; hide sets without scores

Filters combine, are shown as removable chips, and survive a failed reload. Unknown IS/OOS periods are handled honestly: without date filters you can show only unknown-period sets; with date filters, unknown-period sets are included alongside matches rather than silently dropped.

5.4 Columns and result table

Customize columns lets you choose which columns the results table shows (chart sparkline, set, symbol/timeframe, evidence, return, drawdown, profit factor, trades, scores, return/DD and recovery, recovery factor, actions) and restore the defaults. Each metric column header links to the methodology. Rows carry the version state (`current` or `superseded`) and quick actions: open details, download, or add to basket. On small screens the table becomes a card list.

6. Set Pages

The set page is the heart of the portal. It always represents **one exact version**; the header shows creator, publication and update dates, version ordinal ("Version 2 of 5"), and the current/superseded state. If you are looking at a superseded version, a notice links to the current one.

— 6.1 Actions

Download .set (opens the download gate, chapter 9), **Add to basket**, **Compare** (chapter 8), **Favourite**, and **Report content** (chapter 14). Signed-in owners additionally find **Add reports** (chapter 10.8) and successor creation.

— 6.2 Risk flags before performance

Risk and evidence warnings are shown **before** any performance data. Each flag carries a severity (info, caution, elevated, high, extreme), its source (parameter rule, report observation, or factual note), the trigger, and an explanation. Sets with secret-scanner `block` findings cannot be published at all; the set page would show the publication-blocked notice instead.

— 6.3 Parameters

The parameter table lists every parameter with its public value; **Copy parameters** copies them for reuse in MT5. Values the portal cannot interpret are labelled unknown rather than guessed. A parameter diff against the previous version is shown in the version history (added / removed / changed).

— 6.4 Metrics, provenance, and evidence

The metrics section shows the primary figures with their **provenance label** (reported, reconstructed, cross-checked, conflict, derived, unavailable — hover for source report, parser version, and formula). Context includes report format, backtest model, test period, history quality, IS/OOS periods, broker/server, and account/backtest currency (mixed currencies are labelled). Without a parseable report, performance and evidence scores are shown as unavailable — never as zero.

Evidence badges show the class: *No report*, *OHLC report*, *Real-tick report*, *OHLC + real-tick*, plus states like *SHA-256 matched* or *Report conflict*.

— 6.5 Charts

The combined balance/equity chart plots balance (solid) and equity (dashed), with in-sample spans hatched and out-of-sample spans washed green; unknown periods are marked. Real-tick values take precedence where available, OHLC fills the rest. A period key explains the shading. The interactive chart supports hover read-outs and a zoomable/pannable timeline; a data table view shows the underlying observations, and downsampling keeps first, last, and extreme points per bucket. Drawdown and return-percent views are selectable.

— 6.6 Version history

The version list shows every published version with label, change note, and date. The diff view lists parameter changes from the previous version. Every version is permalinked (`/set-versions/...`) and stays downloadable under the same gate.

— 6.7 Licence summary

Each set page summarises the uploader's declarations (own work or licensed rights, no unlawful content) and the upload licence version accepted at publication.

7. Reconstructed Report Pages

The **reconstructed report** page (`/report/...`, linked as "View report details") is a sanitised reconstruction — it never reproduces or links to the uploaded original. Sections:

- **Parser and report provenance** — parser kind and version, state, recognised layout, test model, MT5 build, bars/ticks/symbols, leverage/spread/commission, time-zone confidence, warnings and errors.
- **Set/report association** — which report is primary evidence, which fields were verified against the set parameters, which were unverifiable, and how report-only or ignored parameters were treated. Inherited Ultimate Breakout System defaults are disclosed (with profile version and source hash).
- **Evidence limitations** — a standing explanation that parsing can find inconsistencies but cannot prove who created a report or how the test was run.
- **Summary metrics and provenance** — value, period, provenance, and confidence per metric.
- **Deals-derived reconstruction** — position counts (closed/open/ambiguous, long/short), average reconstruction confidence, monthly aggregates (net P/L, compounded return), position-duration buckets, close-day distribution, and winning-trade concentration.
- **Balance and equity series** — daily values with completeness statistics (series days, days without balance/equity, plotted range), a data-quality timeline, and downsampling notes.
- **Reported/reconstructed reconciliation** — per metric: reported value, reconstructed value, difference, tolerance version, and state (agrees / minor difference / material conflict / not reconstructable).
- **Original report retention** — states that the original stays private, with its SHA-256 hash for verification.

8. Comparing Set Versions

Compare places 2–4 *exact set versions* side by side — neutral comparison, no winner is selected. Three ways to build a selection: the **Compare** action on any set page, checkboxes in the catalogue rows, or pasting set/version links or version IDs into the compare page. The selection lives in the page address, so you can bookmark or share it; a tray at the bottom shows "n of 4 versions selected".

The comparison renders warnings when they apply: mixed evidence classes, non-overlapping or differing IS periods, unknown periods, differing timeframes, or fewer than 30 common daily observations. Sections cover identity and context (creator, symbol, timeframe, IS period, history quality, report formats), metrics with period and source class, scores, aligned curves over the common date range (no normalisation is applied), risk flags, parameter differences (identical / differs / not set everywhere / not set), and evidence completeness.

9. Downloading

— 9.1 The download gate

Every download — single file or basket ZIP — passes the same gate:

1. Choose **Download**. The portal loads the *current* legal documents (Terms, Risk Disclosure, Download Licence).
2. Review the limitations shown: community-supplied files, no verification of profitability or authenticity, backtest limitations, possible loss beyond deposit with leverage, your responsibility for local law, and the note that original reports are never included.
3. If any selected version carries **high or critical** structural-risk flags, an extra warning names it before you can continue.
4. Accept the required confirmations (legal age and lawful use; community uploads are not recommendations; backtest limitations; no advice; acceptance of the current Download Licence and documents). Your acknowledgement is remembered per document version; when a document version changes, you review the new one once.
5. **Drawdown option** — decide whether the portal should write the stored historical maximum equity drawdown into the `HistoricalMaxDD` parameter of the downloaded `.set` files:
 - *Yes — overwrite*: writes the maximum equity drawdown from the stored reports into every downloaded file, replacing any existing value.
 - *Only if unset*: fills `HistoricalMaxDD` only where it is missing, empty, or 0.
 - *No — keep files unchanged*: downloads the stored parameter files exactly as uploaded.

Two caveats are shown with this option: if you run a set in "risk per strategy" mode and your broker's contract size differs from the one in the stored reports, the value may need manual adjustment (contract size changes the derived position sizes); drawdown values are amounts in each report's account currency, and sets without a stated equity drawdown keep their file unchanged.

6. The portal creates a **one-time link** that expires in about 300 seconds and works exactly once. If the transfer does not complete, request another link.

Downloads can be refused with explicit error states: disabled downloads, jurisdiction restrictions, changed legal documents, expired/consumed links, bundles not ready, removed versions, or rate limiting.

— 9.2 The download basket

Add exact versions to the basket from any set page or catalogue row (up to **50 items**). The basket lives on your device and merges with your account when you sign in. Items warn when a **newer version exists**, and versions that are no longer downloadable are excluded from the bundle with a note. **Prepare basket ZIP** creates an immutable snapshot: the ZIP contains the approved `.set` files (with your chosen drawdown

option applied) plus a server-generated README and a manifest with SHA-256 hashes for every file. The bundle link is ready after a short preparation period, expires after **72 hours**, and can be re-downloaded until then. Aggregate bundle contents are limited to 32 MiB.

Counted downloads are deduplicated per set version and browser/account over 24 hours; the number is a usage indicator, not a count of unique people.

10. Uploading And Publishing Sets

10.1 Prerequisites and formats

Uploading requires a signed-in, email-verified account. Accepted files: `.set`, MT5 reports (`.html`, `.htm`, `.xlsx`), and ZIP archives. Limits: 20 MiB per direct file, 100 MiB per ZIP (250 MiB decompressed), at most 100 files per batch, and a ZIP must be uploaded alone. Supporting images are not accepted in this release.

10.2 The wizard

Step	What happens
1 — Add files	Drag <code>.set</code> files or a ZIP (or choose them). Reports are optional; a ZIP may contain several sets — each <code>.set</code> becomes its own reviewed draft.
2 — Processing	Files are transferred to a private quarantine , malware-scanned, extracted, parsed, and matched. You can leave and resume; nothing is public during processing.

While step 2 runs, the processing panel shows one **stage rail per file** — queued, uploading, virus scan, parsing, processed — plus an overall progress percentage. If no status changes for a while, the panel says so explicitly (large reports can take several minutes); after several minutes of silence it suggests restarting the batch with the same files, and nothing was made public by then. As soon as every file is processed, a **continue** button takes you to the set details. | 3 — Set details | Per draft: associate the reports that belong to the set (filename similarity is only a hint), then complete the metadata. | | 4 — Review & publish | Review findings, confirm the declarations, attest each set, publish. |

10.3 Report association and matching

For every set draft the portal suggests reports from the same batch (same-folder hints, parameter similarity percentage). Association triggers a **factual parameter comparison** with states: *exact factual match*, *match with unverifiable fields*, *mismatch*, *insufficient report data*. Only matching reports can be published as evidence; a mismatching report stays private. One report is chosen as the **primary report** (the one used for scores). EA names and broker metadata never block matching — parameter values, symbol, timeframe, and test settings are what count.

10.4 Metadata

Required per draft: title, canonical symbol, raw broker symbol, timeframe, broker (search existing entries first; creating a new broker requires a confirmation that it is genuinely new — community-supplied brokers are marked as such until curated), server, and the IS/OOS optimisation period (both IS dates, optionally both OOS dates, or an explicit "unknown" declaration — the portal never infers dates). Optional: factual description, factual tags, predecessor version, your version label, and a change note (required for successors).

— 10.5 Review findings

The review step shows per draft: parsed parameters (with unknown/duplicate keys), **secret/privacy findings** (credential-like names, private keys, wallet keys, JWT-like tokens, high-entropy tokens, email addresses, account numbers, IP addresses, home paths, credential URLs). Blocking findings pause publication — replace the file locally and start a replacement batch; flagged bytes stay private. Risk flags, report quality, parser identity and issue counts, calculable scores, and publication validation (missing fields, blockers) complete the picture.

— 10.6 Declarations and publication

Publishing requires five declarations, recorded with the exact document versions: rights (own work / licensed), Upload Licence grant, no unlawful or credential material, historical-data acknowledgement with the Risk Disclosure, and acceptance of the current Terms. Each selected set gets its own per-file attestation; unchecked drafts stay private. After confirmation the published bytes and metadata snapshot are **immutable** — corrections require a successor version. The final screen shows what became public (set bytes and metadata) and what stayed private (original reports), with the published version ID and a direct link.

— 10.7 When processing finds problems

Failed files are never published. The wizard explains each case with a recovery action: replace files via a **replacement batch** (corrupt ZIPs, malware findings, unsupported layouts, oversized files), fix metadata or period fields, re-associate reports, or cancel the batch (unpublished drafts are discarded; already published versions remain). Distinct error messages exist for every archive problem — signature mismatch, unsafe paths, too many entries, decompression bombs, and so on.

— 10.8 After publication

- **Add reports:** open your published set and choose **Add reports** to attach later evidence (e.g. the real-time run). Reports are scanned, parsed, and compared with the published parameters; only mismatch-free reports are attached. The set file and metadata stay unchanged.
- **Successors:** to correct a set, upload a new version with a change note; history stays visible.
- **Unfinished business:** everything unpublished waits under Account → Upload batches.
- **Portfolio offer:** when one upload published two or more sets, the portal offers to combine them into a portfolio (chapter 11).

11. Portfolios

Portfolios combine published sets into one hypothetical performance curve. The feature is server-flagged; when disabled, the navigation hides it.

— 11.1 Creating one

From **Portfolios** → **Create portfolio**: name and optional factual description, then add published sets by search or by pasting set links, `/set-versions` links, or bare version IDs. Give each component a **factor** (default 1) that scales its deals (2 doubles, 0.5 halves). The portfolio starts at the **average of the components' start capitals**; there is no optimisation and no execution — factors are manual. Creating it starts a background calculation from the combined deal lists.

— 11.2 Reading one

The portfolio page shows: the portfolio curve plus every component at its proportional share — the chart plots **accumulated gains from a zero baseline**, not the account balance, and the price scale rescales when lines are hidden — with each distinct declared in-sample window shaded in its own colour (identical windows share one band; the legend lists every distinct window and how many sets share it) and out-of-sample spans green; component lines carry their last gain across days without deals so each reads as a continuous curve; clicking a series label in the legend hides or restores that line and the price scale rescales to what remains visible; portfolio metrics (return, drawdown, profit factor, Sharpe, trade counts, balances — drawdown and recovery are **balance-only**, equity drawdown is not available for portfolios and the page says so); a **daily PnL correlation matrix** (Pearson over shared days, days without deals count as 0); and the component table with factor, scaled deposit, trades, and eligibility reasons for any excluded set.

— 11.3 Versions and visibility

Saving component changes creates a **new portfolio version**; published versions stay untouched. Visibility: **private** (only you), **unlisted** (reachable by link), **public** (listed in the catalogue). Portfolios can be deleted with all versions. Every public portfolio page carries a mandatory limitation notice: portfolio analytics are a hypothetical combination of separate historical reports — they do not simulate shared margin, execution conflicts, correlated slippage, broker limits, simultaneous order handling, liquidity, or live account behaviour, and they are not a recommendation. The portfolio ZIP download passes the same gate as set downloads (chapter 9) and contains the member sets.

12. Creators And Brokers

— 12.1 Creators

The **Creators** directory lists public profiles with search; it never ranks or endorses. A creator profile shows member-since, current public sets (superseded versions optional), counted downloads, followers, latest publication, and a **Follow** button (followers appear in your account area and can drive notification rules). Profiles carry the same **Report content** action as sets.

— 12.2 Brokers

The **Brokers** directory lists broker contexts with server variants, aliases, and symbol variants, each marked **community supplied** or **curated**. Broker context is uploader-supplied metadata — the portal states plainly that it is not an endorsement or rating. Each entry shows how many current set versions use it and offers **Propose a correction**. The catalogue's broker filter uses the same taxonomy.

13. Notifications

Two mechanisms, both opt-in:

- **Daily match digest (no account needed)** — under *Notifications*, enter an email address, choose filters, and consent. A confirmation email (double opt-in) activates the subscription. At most one email per day is sent, and only when there are matches; every email carries an unsubscribe link.
- **Account notification rules** — per rule: event (*new set published*, *successor published*, *followed creator publishes*, *selected set restricted/updated*), channel (web or daily email), pause/resume, and a **send test preview** button. Digest emails state why each entry matched ("Matched because ..."); an empty day sends nothing.

14. Scores, Methodology, And Trust

14.1 The five scores

All scores are 0–100, computed by published, versioned formulas from the supplied evidence — never manually edited.

Score	Direction
Historical Test Score	Higher = longer, better-documented test history
Risk Index	Higher = more observed or structural risk in the supplied evidence
Robustness Index	Higher = results hold up better out-of-sample
OHLC/RT Fidelity	Higher = OHLC-model and real-tick reconstructions agree
Evidence Confidence	Higher = more complete, verifiable evidence base

Missing inputs are handled with neutral substitutions (50) or marked incomplete — never treated as good or bad. Each score page shows its components, definition version, and a standing disclosure: scores describe user-supplied test evidence under a published formula — not advice, verification, or a forecast.

14.2 Methodology page

The **Methodology** page (versioned, immutable, dated) documents scope and neutrality, every metric definition, parser and provenance states, each score formula, IS/OOS handling, structural flags, download counting, and the changelog with effective dates.

14.3 Moderation, notices, and appeals

- **Report content** — a simple form for misleading claims, intellectual property, personal data, or spam, with a receipt reference and a public status check.
- **Notice & Action** — the formal channel for rights holders and legal claims: legal basis, good-faith and authority declarations, receipt reference, acknowledgement within the legal period, and a status page with state and decision deadline.
- **Appeals** — moderation decisions can be appealed with the link token from the decision notice (signed in: the decision ID), and are reviewed within 30 days by someone not involved in the original decision.
- **Country access** — content or downloads can be restricted per jurisdiction (HTTP 451 explains itself).
- **Status** — the public status page shows database, queue, and object-storage health without exposing infrastructure details. It reflects the platform itself: if the site otherwise works, an unreachable probe is a reporting gap rather than an outage.

- **Legal documents** — Terms, Privacy Notice, Risk Disclosure, Upload Licence, Download Licence, Acceptable Use Policy, combined Notice & Action and Moderation Policy, Accessibility Statement, Cookie & Storage Notice, Country Access Policy, and Imprint. Each document is versioned with an effective date, drafts carry a pending-counsel-review banner, and every document offers a printable view.

15. Error Pages And Limits

Situation	What you see
403	Content restricted for legal, privacy, security, rights, or moderation reasons
404	Page does not exist, was removed, or is not public
410	Content removed
451	Not available in your jurisdiction (country access rules)
500	Unexpected error — try again later

Hard limits at a glance: basket 50 versions; bundle contents 32 MiB; bundle link 72 h; download link 300 s, one use; uploads 100 files/batch, 20 MiB direct, 100 MiB ZIP; comparison 4 versions.

16. The Operator Console (Administration)

The admin area is for the portal operator. It requires **step-up authentication** (a fresh passkey verification), and destructive or sensitive actions need a **reason** and, where configured, a **second authorised reviewer** (four-eyes). Every privileged mutation is written to the audit log.

Areas: dashboard (failed/stuck jobs, unsupported parser layouts, quarantine findings, open notices/appeals/privacy requests, expiring restrictions, email health, storage); uploads & quarantine; sets & versions (flag/hide/quarantine/remove with stated grounds, restore); reports & parsers (reparse, recalculate); scores & methodology (scores **cannot** be edited manually – corrections run through new definition versions and recalculation); users & restrictions (warnings, upload restrictions, temporary/permanent locks, session revocation, scoped IP restrictions with review dates); brokers & symbols (**taxonomy**: canonical symbols with asset classes and reviewed aliases; broker curation states); content reports & notices; appeals; authority orders & legal holds; privacy requests (export/deletion execution); country access; notifications & email; bundles & download abuse; **feature flags** (server-authoritative; they can never bypass immutable publication, legal acceptance, quarantine, or permission checks); audit log; transparency reporting; and system health.

Appendix: Glossary

Term	Meaning
Set / <code>.set</code> file	A parameter file for the Ultimate Breakout System EA
Set version	One immutable, published snapshot of a set; corrections create successors
Evidence	An MT5 backtest report (HTML or XLSX) supplied by the uploader
OHLC / real-tick	Backtest models; real-tick uses every real tick and is the stronger evidence class
IS / OOS	In-sample (optimisation period) and out-of-sample (test period) of a backtest
Provenance	How a displayed value was determined: reported, reconstructed, cross-checked, derived, conflict, or unavailable
Reconstruction / reconciliation	Metrics recalculated by the portal from the deals in a report — and their comparison against the reported value
Score	A 0–100 factual measure of one documented aspect (history, risk, robustness, fidelity, evidence)
Risk flag	A structural warning derived from parameters or report observations
Portfolio	A hypothetical combination of published sets, recalculated from their deal lists
Bundle / basket ZIP	A server-generated ZIP of exact set versions with manifest and README

This manual is maintained in the repository (`docs/manual/`) together with the source that renders it, and is linked from the site footer and the Help page. When a feature ships or changes, the manual is updated in the same change — see `AGENTS.md`.